



	Vision	Boomerang	Standard Mount	Under Mount	Hydraulic Mount
Warranty	Lifetime Limited	Lifetime Limited	Lifetime Limited	Lifetime Limited	Lifetime Limited
Material	Galvalume	Galvalume	Galvalume	Galvalume	Galvalume
	Aircraft Aluminum	Aircraft Aluminum	Aircraft Aluminum	Aircraft Aluminum	Aircraft Aluminum
Weight	28 lbs	28 lbs	21 lbs	29lbs	23 lbs
Position below Hottub	Fully Below	Fully Below	Mount will determine	Slightly Below	Slightly below
Operation Assistance	Dual Gas Shocks	Dual Gas Shocks	Manual	Manual	Dual Gas Shocks
Clearance Required	10-14" Rear/5"Side	10-14" Rear/5"Side	12-14" Rear/5" Side	16" Rear/5" Side	12-14"Rear/5"Side
Maximum Cover Width	98"	98"	109"	109"	109"
Spa Height	Standard	Standard	Extensions Available	Extensions available	Standards
Locations to Close	Either Side	Either Side	Either Side	Either Side	Either Side
Locations to Open	Either Side	Either Side	Either Side	Either Side	Either Side
Max Corner Radius	20"	20"	16"	16"	16"
Corner Radius Extension	N/A	N/A	Available	Available	Available
OK for In-Deck Spas?	No	No	Optional	No	Requires 5" Rise
OK on Round Spas?	No	No	Yes-Deck Mount Only	No	Yes- In-ground only
Cover View when open	Open View	Open View	Mount will determine	Partial interior View	Whole Cover Interior
Requires Special Cover	No	No	No	No	No
Foam Handle Included	Yes	Yes	Yes	Yes	Yes